



Synchronization and Chaos Control Using a Single Controller of Five Dimensional Autonomous Homopolar Disc Dynamo

Lucienne Makouo ^{a,1}, Alex Stephane Kemnang Tsafack ^{b,2,*}, Marceline Motchongom Tingue ^{c,3}, André Rodrigue Tchamda ^{d,4}, Sifeu Takougang Kingni ^{e,5}

^a Department of Civil Engineering and Architecture, National Higher Polytechnic Institute, University of Bamenda, P.O. Box 39, Bamenda, Cameroon

^bResearch unit of Condensed Matter of Electronics and Signal Processing, Department of Physics, Faculty of Sciences, University of Dschang, P. O. Box 67, Dschang, Cameroon

^c Higher Technical Teachers Training College Polytechnic Institute, University of Bamenda, P.O. Box 39, Bamenda, Cameroon

^d Department of Rural Engineering, Faculty of Agronomy and Agricultural Sciences, University of Dschang, P. O Box 222, Dschang, Cameroon

^e Department of Mechanical, Petroleum and Gas Engineering, Faculty of Mines and Petroleum Industries, University of Maroua, P. O. Box 46, Maroua, Cameroon

¹makouol@yahoo.fr; ²alexstephanekemnang@gmail.com; ³tinguemax@yahoo.fr; ⁴rodriguetchamda@yahoo.fr;

⁵ stkingni@gmail.com

* Corresponding Author

ARTICLE INFO

Article history

Received 20 June 2021 Revised 19 July 2021 Accepted 22 July 2021

Keywords

Five-dimensional autonomous homopolar disc dynamo; Hyperchaos; Electronic implementation; Synchronization; Chaos control; Hyperchaos control; Single controller

ABSTRACT

The electronic implementation, synchronization, and control of hyperchaos in a five-dimensional (5D) autonomous homopolar disc dynamo are investigated in this paper. The hyperchaotic behavior is found numerically using phase portraits and time series in 5D autonomous homopolar disc dynamo is ascertained on Orcad-PSpice software. The synchronization of the unidirectional coupled 5D hyperchaotic system is also studied by using the feedback control method. Finally, hyperchaos found in 5D autonomous homopolar disc dynamo is suppressed thanks to the designed single feedback. Numerical simulations and electronic implementation reveal the effectiveness of the single proposed control.

This is an open-access article under the CC-BY-SA license.



1. Introduction

Chaotic behavior has many applications in various fields of science. Unfortunately, chaotic behaviors are a source of instability and disturbance in some dynamic systems. Therefore, it is interesting to control chaotic behavior in such dynamical systems. Many authors proposed methods to suppress chaos such as resonant parametric perturbation control [1], generalized predictive control [2], adaptive control [3, 4], the input-output linearization control [5], frequency domain analysis control [6, 7], zero spectral radius control [8], optimal control [9], sliding mode control [10], single feedback control [11] and various other control methods. The single feedback control technique is concise, simple, and easy to realize. A single feedback



control method is used to control hyperchaos in 5D autonomous homopolar disc dynamo [12] in this paper.

On the other hand, since Pecora and Caroll [13] demonstrated the synchronization between chaotic coupled dynamical systems, a multitude of papers devoted to the synchronization of chaotic systems [14-18]. Several types of synchronization known as complete synchronization [13], offset synchronization [19], generalized synchronization [20-22], projective synchronization [23-27], modified projective synchronization [28], function projective synchronization [29] and various other synchronizations. A technique for synchronizing a chaotic four-dimensional system using a feedback controller, a single variable, has been proposed and demonstrated in [30]. Recently, the authors of [31] investigated the dynamics, chaos control, and synchronization in autonomous homopolar dynamo systems. The authors of [32] studied the existence of Hopf bifurcation and synchronization by using a new fuzzy controller in a 5D autonomous homopolar disc dynamo system.

Based on contributions from previous works, this paper opted to study analytically and numerically the feedback synchronization of unidirectional coupled 5D autonomous homopolar disc dynamo and chaos control using a single controller in this paper. These constitute a significant contribution to the best of our knowledge and complement of some earlier works.

The paper is structured in five sections: The rate equations and circuit design of the 5D autonomous homopolar disc dynamo are described in Section 2. A feedback synchronization of a unidirectional coupled 5D hyperchaotic system is studied in Section 3. In Section 4, the single controller is used to control hyperchaos in the 5D hyperchaotic. Section 5 concludes this paper.

2. Rate equations and circuit design of 5D autonomous homopolar disc dynamo

The rate equations of 5D autonomous homopolar disc dynamo are [12]

$$\frac{dx}{dt} = r(y-x) + w, \tag{1a}$$

$$\frac{dy}{dt} = -(1+m)y + xz - v, \tag{1b}$$

$$\frac{dz}{dt} = g \left[1 + mx^2 - (1+m)xy \right], \tag{1c}$$

$$\frac{d\mathbf{w}}{dt} = 2(1+m)\mathbf{w} + xz - k_1 x, \tag{1d}$$

$$\frac{d\mathbf{v}}{dt} = -m\mathbf{v} + k_2 y,\tag{1e}$$

Where variables x, y, z, w, v are the state variables and t are the time, the parameters g, m, r, k_1, k_2 are positive reals. System (1) exhibits hyperchaotic behavior for given values of parameters, as shown in Fig. 1. The parameter is r = 8, m = 0.04, g = 140.6, $k_1 = 34$, and $k_2 = 12$. The initial conditions of (x, y, z, w, v) are (0.05, -0.5, 0.1, -1, 2). The electronic circuit of the system (1) is implemented on the Orcard-PSpice software and is depicted in Fig. 2.



Fig. 1. Hyperchaotic attractor in system (1) for r = 8, m = 0.04, g = 140.6, $k_1 = 34$, and $k_2 = 12$.



Fig. 2. The electronic circuit describing system (1).

The circuit of Fig. 2 is made of resistors, capacitors, operational amplifiers, and analog multiplier devices. Resistors and capacitor values are $R_a = 10k\Omega$, $R_b = 12.5k\Omega$, $R_c = 12.5k\Omega$, $R_d = 98.154k\Omega$, $C_1 = C_2 = C_3 = C_4 = C_5 = 1n$ F, $R_e = 100k\Omega$, $R_f = 100k\Omega$, $R_g = 6.84k\Omega$, $R_h = 177.81k\Omega$, $R_i = 100k\Omega$, $R_j = 29.41k\Omega$, $R_k = 100k\Omega$, $R_l = 48.08k\Omega$, $R_m = 2500k\Omega$, $R_n = 83.33k\Omega$, $R_1 = R_2 = R_4 = R_5 = R_3 = 10k\Omega$, $R_6 = R_7 = R_8 = R_{10} = R_9 = 10k\Omega$, $R_{12} = R_{13} = R_{14} = R_{15} = 10k\Omega$, $V_{cc} = 14.06V$. The phase planes obtained from Fig. 2 are depicted in Fig. 3. The phase planes of Fig. 3 and the one of Fig. 1 confirm each other.



Fig. 3. Phase planes of hyperchaotic attractors are obtained from the electronic circuit of the system (1).

3. Synchronization of unidirectional coupled 5D autonomous homopolar disc dynamo

The drive and the response 5D hyperchaotic systems are expressed, respectively as

$$\frac{dx_1}{dt} = r\left(y_1 - x_1\right) + w_1,\tag{2a}$$

$$\frac{dy_1}{dt} = -(1+m)y_1 + x_1z_1 - v_1,$$
(2b)

$$\frac{dz_1}{dt} = g \left[1 + mx_1^2 - (1+m)x_1y_1 \right],$$
(2c)

$$\frac{d\mathbf{w}_{1}}{dt} = 2(1+m)\mathbf{w}_{1} + x_{1}z_{1} - k_{1}x_{1},$$
(2d)

$$\frac{d\mathbf{v}_1}{dt} = -m\mathbf{v}_1 + k_2 y_1,\tag{2e}$$

$$\frac{dx_2}{dt} = r(y_2 - x_2) + w_2 + u_1,$$
(3a)

$$\frac{dy_2}{dt} = -(1+m)y_2 + x_2z_2 - v_2,$$
(3b)

$$\frac{dz_2}{dt} = g \left[1 + mx_2^2 - (1+m)x_2y_2 \right] + u_2,$$
(3c)

$$\frac{dw_2}{dt} = 2(1+m)w_2 + x_2z_2 - k_1x_2 + u_3,$$
(3d)

$$\frac{d\mathbf{v}_2}{dt} = -m\mathbf{v}_2 + k_2 y_2,\tag{3e}$$

Where u_1, u_2 and u_3 are the controllers. The synchronization errors are defined as follows: $e_1 = x_2 - x_1$, $e_2 = y_2 - y_1$, $e_3 = z_2 - z_1$, $e_4 = w_2 - w_1$ and $e_5 = v_2 - v_1$. Its derivatives are given as

$$\frac{de_1}{dt} = r(e_2 - e_1) + e_4 + u_1, \tag{4a}$$

$$\frac{de_2}{dt} = -(1+m)e_2 + z_2e_1 + x_1e_3 - e_5,$$
(4b)

$$\frac{de_3}{dt} = gm(x_1 + x_2)e_1 - (1+m)(y_2e_1 + x_1e_2) + u_2,$$
(4c)

$$\frac{de_4}{dt} = 2(1+m)e_4 + z_2e_1 + x_1e_3 - k_1e_1 + u_3,$$
(4d)

$$\frac{de_5}{dt} = -me_5 + k_2e_2. \tag{4e}$$

By choosing the controllers $u_1 = -re_2 - e_4$, $u_2 = -e_3 + (1+m)x_1e_2$ and $u_3 = -3(1+m)e_4$, system (4) becomes

$$\frac{de_1}{dt} = -re_1,\tag{5a}$$

$$\frac{de_2}{dt} = -(1+m)e_2 + z_2e_1 + x_1e_3 - e_5,$$
(5b)

$$\frac{de_3}{dt} = -e_3 + gm(x_1 + x_2)e_1 - (1+m)y_2e_1,$$
(5c)

$$\frac{de_4}{dt} = -(1+m)e_4 + z_2e_1 + x_1e_3 - k_1e_1,$$
(5d)

$$\frac{de_5}{dt} = -me_5 + k_2e_2. \tag{5e}$$

The solution of (5a) is $e_1(t) = e_1(0)e^{-rt}$. So $\lim_{t \to \infty} e_1(t) = 0$ and system (5) becomes

$$\frac{de_2}{dt} = -(1+m)e_2 + x_1e_3 - e_5,$$
(6a)

$$\frac{de_3}{dt} = -e_3,$$
(6b)

$$\frac{de_4}{dt} = -(1+m)e_4 + x_1e_3,$$
(6c)

$$\frac{de_5}{dt} = -me_5 + k_2e_2. \tag{6d}$$

The solution of (6b) is $e_3(t) = e_3(0)e^{-t}$. Thereafter $\lim_{t \to \infty} e_3(t) = 0$ and system (6) is reduced to

$$\frac{de_2}{dt} = -(1+m)e_2 - e_5,$$
(7a)

$$\frac{de_4}{dt} = -(1+m)e_4,\tag{7b}$$

$$\frac{de_5}{dt} = -me_5 + k_2e_2. \tag{7c}$$

The solution of (7b) is $e_4(t) = e_4(0)e^{-(1+m)t}$. Thereafter $\lim_{t\to\infty} e_4(t) = 0$ and system (7) is reduced to:

$$\begin{pmatrix} \frac{de_2}{dt} \\ \frac{de_5}{dt} \end{pmatrix} = \begin{pmatrix} -1-m & -1 \\ k_2 & -m \end{pmatrix} \begin{pmatrix} e_2 \\ e_5 \end{pmatrix} = A \begin{pmatrix} e_2 \\ e_5 \end{pmatrix}.$$
(8)

For m = 0.04 and $k_2 = 12$, the eigenvalues of A at the equilibrium point $(e_2 = 0, e_5 = 0)$ are $\lambda_{1,2} = -0.54 \pm 3.42782730020052 j$ with $j^2 = -1$. So, system (8) is asymptotically stable.

ISSN 2775-2658

controllers $u_1 = -re_2 - e_4$, $u_2 = -e_3 + (1+m)x_1e_2$ and $u_3 = -3(1+m)e_4$ can Therefore, the synchronize the drive system (2) and the response system (3). The synchronization errors are depicted in Fig. 4. The controllers u_1, u_2 and u_3 are activated at $t \ge 1400$. The initial $(x_1(0), y_1(0), z_1(0), w_1(0), v_1(0)) =$ conditions of systems (2)and (3) are $(x_2(0), y_2(0), z_2(0), w_2(0), v_2(0)) = (0.5, -0.5, 0.1, -1, 2),$ (0.05, -0.5, 0.1, -1, 2)and respectively. Fig. 4 reveals the effectiveness of the synchronization between system (2) and system (3).



Fig. 4. Time series of synchronization errors for r = 8, m = 0.04, g = 140.6, $k_1 = 34$, and $k_1 = 12$.

4. Hyperchaoscontrol of 5D autonomous homopolar disc dynamo via a single controller

System (1) with the controller u_4 becomes

$$\frac{dx}{dt} = r(y-x) + w, \tag{9a}$$

$$\frac{dy}{dt} = -(1+m)y + xy - v, \tag{9b}$$

$$\frac{dz}{dt} = g \left[1 + mx^2 - (1+m)xy \right] + u_4, \qquad (9c)$$

$$\frac{d\mathbf{w}}{dt} = 2(1+m)\mathbf{w} + xz - k_1 x, \tag{9d}$$

$$\frac{d\mathbf{v}}{dt} = -m\mathbf{v} + k_2 \mathbf{y}.$$
(9e)

By choosing $u_4 = -z - g \left[1 + mx^2 - (1 + m)xy \right]$, system (9) becomes:

$$\frac{dx}{dt} = r(y-x) + w, \tag{10a}$$

$$\frac{dy}{dt} = -(1+m)y + xz - v, \tag{10b}$$

$$\frac{dz}{dt} = -z,$$
(10c)

$$\frac{d\mathbf{w}}{dt} = 2(1+m)\mathbf{w} + xz - k_1 x, \tag{10d}$$

$$\frac{d\mathbf{v}}{dt} = -m\mathbf{v} + k_2 \mathbf{y}.$$
(10e)

The solution of (10c) is $z(t) = z(0)e^{-t}$. So $\lim_{t \to \infty} z(t) = 0$ and system (10) becomes:

$$\begin{pmatrix} \frac{dx}{dt} \\ \frac{dy}{dt} \\ \frac{dw}{dt} \\ \frac{dw}{dt} \\ \frac{dv}{dt} \\ \frac{dv}{dt} \\ \frac{dv}{dt} \end{pmatrix} = \begin{pmatrix} -r & r & 1 & 0 \\ 0 & -(1+m) & 0 & -1 \\ k_1 & 0 & 2(1+m) & 0 \\ 0 & k_2 & 0 & -m \end{pmatrix} \begin{pmatrix} x \\ y \\ w \\ v \end{pmatrix} = B \begin{pmatrix} x \\ y \\ w \\ v \end{pmatrix}.$$
(11)

For r = 8, m = 0.04, $k_1 = 34$, and $k_2 = 12$, the eigenvalues of B at the equilibrium point (x = 0, y = 0, w = 0, v = 0) are $\lambda_{5,6} = -2.96 \pm 2.9323028492978j$ and $\lambda_{5,6} = -0.54 \pm 3.42782730020052j$ with $j^2 = -1$. So, system (11) is asymptotically stable. Therefore, the hyperchaotic behavior found in the system (1) is controlled using the controller $u_4 = -z - g \left[1 + mx^2 - (1 + m)xy \right]$.

The time evolutions of the state variables and the controller u_4 are shown in Fig. 5. The controller u_4 is activated at $t \ge 1300$. The initial conditions are (x(0), y(0), z(0), w(0), v(0))=(0.05,-0.5, 0.1,-1, 2). Fig. 5 demonstrates that the control of hyperchaos system (1) using the controller $u_4 = -z - g \left[1 + mx^2 - (1+m)xy \right]$ is effective. The electronic implementation of the controlled system (9) is obtained from the electronic implementation of the system (1) in Fig. 2 as shown in Fig. 6.

The circuit of Fig. 6 has 32 resistors, 5 capacitors, 13 operational amplifiers, 3 analog multiplier devices, and 1 switcher. Resistors and capacitor values are $R_a = 10k\Omega$, $R_b = 12.5k\Omega$, $R_c = 12.5k\Omega$, $R_d = 98.154k\Omega$, $C_1 = C_2 = C_3 = C_4 = C_5 = 1nF$, $R_e = 100k\Omega$, $R_f = 100k\Omega$, $R_g = 6.84k\Omega$, $R_h = 177.81k\Omega$, $R_i = 100k\Omega$, $R_j = 29.41k\Omega$, $R_k = 100k\Omega$, $R_l = 48.08k\Omega$, $R_m = 2500k\Omega$, $R_n = 83.33k\Omega$, $R_1 = R_2 = R_4 = R_5 = R_3 = 10k\Omega$, $R_6 = R_7 = R_8 = R_{10} = R_9 = 10k\Omega$, $R_{12} = R_{13} = R_{14} = R_{15} = 10k\Omega$, $V_{cc} = 14.06V$.



Fig. 5. Time evolutions of *x*, *y*, *w*, *v* and u_4 for r = 8, m = 0.04, g = 140.6, $k_1 = 34$ and $k_2 = 12$



Fig. 6. The electronic circuit is describing the controlled system (9).

ISSN 2775-2658

The time evolutions of the state responses and the output of the single controller generated from the circuit of the controlled system (9) are shown in Fig. 7. The time evolutions of Fig. 7 and the one of Fig. 5 confirm each other.



Fig. 7. Time evolutions of the controlled system (9) are obtained from Fig. 6.

5. Conclusion

The electronic implementation, synchronization, and control of hyperchaos in fivedimensional autonomous homopolar disc dynamo were investigated in this paper. The designed circuit of the five-dimensional autonomous homopolar disc dynamo was realized on Orcad-PSpice software to ascertain the hyperchaotic behavior found during the numerical simulations. The synchronization of unidirectional coupled five-dimensional autonomous homopolar disc dynamo was achieved by using the feedback control method. Finally, it was theoretically and electronically proven that the proposed single controller can control the hyperchaotic behavior of the five-dimensional autonomous homopolar disc dynamo.

References

- [1] R. Lima and M. Pettini, "Suppression of chaos by resonant parametric perturbations," *Physical Review A*, vol. 41, no. 2, pp. 726-733, 1990. https://doi.org/10.1103/PhysRevA.41.726
- [2] K.-S. Park, J.-B. Park, Y.-H. Choi, T.-S. Yoon and G. Chen, "Generalized predictive control of discrete time chaotic systems," *International Journal of Bifurcation and Chaos*, vol. 8, no. 7, pp. 1591-1587, 1998. https://doi.org/10.1142/S0218127498001248
- [3] S. Boccaletti and F. T. Arecchi, "Adaptive recognition and control of chaos," *Physica D: Nonlinear Phenomena*, vol. 96, no. 1-4, pp. 9-16 1996. https://doi.org/10.1016/0167-2789(96)00010-3

- [4] A. C. H. Mevay and R. Sarpeshkar, "Predictive comparators with adaptive control," *IEEE Transaction on Circuits and Systems II: Analog and Digital Signal Processing*, vol. 50, no. 9, pp. 579-588, 2003. https://doi.org/10.1109/TCSII.2003.815026
- [5] X. Yu, "Controlling chaos using input-output linearization approach," International Journal of Bifurcation and Chaos, vol. 7, no. 7, pp. 1659-1664, 1997. https://doi.org/10.1142/S021812749700128X
- [6] R. Genesio, A. Tesi and F. Villoresi, "A frequency approach for analyzing and controlling chaos in nonlinear circuits," *IEEE Transaction on Circuits and Systems I: Fundamental Theory and Applications*, vol. 40, no. 11, pp. 819-828, 1993. https://doi.org/10.1109/81.251820
- M. Basso, R. Genesio and A. Tesi, "Frequency domain methods and control of complex dynamics," Proc. 37 IEEE Conf. Decision & Control, USA, pp. 1936-1941, 1998. https://doi.org/10.1109/CDC.1998.758599
- [8] P. Chanfreau and H. Lyyjynen, "Viewing the efficiency of chaos control," *Journal of Nonlinear Mathematical Physics*, vol. 6, no. 3, pp. 314-331, 1999. https://doi.org/10.2991/jnmp.1999.6.3.7
- [9] S. Gadaleta and G. Dangelmayr, "Optimal chaos control through reinforcement learning," *Chaos*, vol. 9, no. 3, pp. 775-788, 1999. https://doi.org/10.1063/1.166451
- [10] H.T. Yau, C.K. Chen, and C.L Chen, "Sliding mode control of chaotic systems with uncertainties," *International Journal of Bifurcation and Chaos*, vol. 10, no. 5, pp. 1139-1147, 2000. https://doi.org/10.1142/S021812740000803
- [11] A. Cheukem, A. S. K. Tsafack, S. T. Kingni, A. C. Chamgoué and J. R. M. Pone, "Permanent magnet synchronous motor: chaos control using single controller, synchronization and circuit implementation," *SN Applied. Sciences*, vol. 2, p. 420, 2020. https://doi.org/10.1007/s42452-020-2204-7
- [12] Z. Wei, I. Moroz, J. C. Sprott, A. Akgul and W. Zhang, "Hidden hyperchaos and electronic circuit application in a 5D self-exciting homopolar disc dynamo," *Chaos*, vol. 27, no. 3, pp. 033101-033110, 2017. https://doi.org/10.1063/1.4977417
- [13] L. M. Pecora and T. L. Carroll, "Synchronization in chaotic systems," *Phys. Rev. Lett.*, vol. 64, no. 8, pp. 821-825, 1990. https://doi.org/10.1103/PhysRevLett.64.821
- [14] N. F. Rulkov, K. M. Sushchik, L. S. Tsimring, and H. D. I. Abarbanel, "Generalized synchronization of chaos in directionally coupled chaotic systems", *Phys. Rev. E*, vol. 51, no. 2, pp. 980-994, 1995. https://doi.org/10.1103/PhysRevE.51.980
- [15] R. Mainieri and J. Rehacek, "Projective synchronization in three-dimensional chaotic systems," *Phys.Rev. Lett.*, vol. 82, no. 15, pp. 3042-3045, 1999. https://doi.org/10.1103/PhysRevLett.82.3042
- [16] T. Yang and L. Chua, "Impulsive stabilization for control and synchronization of chaotic systems: Theory and application to secure communication," *IEEE Transactions on Circuits and Systems I: Fundamental Theory and Applications*, vol. 44, no. 10, pp. 976-988, 1997. https://doi.org/10.1109/81.633887
- [17] K. W. Wong, J. Y. Chen, and L. M. Cheng, "A secure communication scheme based on the phase synchronization of chaotic systems," *Chaos: An Interdisciplinary Journal of Nonlinear Science*, vol. 13, no. 2, pp. 508-514, 2003. https://doi.org/10.1063/1.1564934
- [18] A. Loria, E. Panteley, and A. Zavala., "Adaptive observers with persistency of excitation for synchronization of chaotic systems," *IEEE Transactions on Circuits and Systems I: Regular Papers*, vol. 56, no. 12, pp. 2703-2716, 2009. https://doi.org/10.1109/TCSI.2009.2016636
- [19] M. Diao, Y. G. Yu, S. Wang, and J. Z. Yu, "Hybrid lag function projective synchronization of discrete chaotic systems with di§erent orders," *Inter. J. Nonl. Sci. Num. Simu.*, vol. 11, no. 7, pp. 503-508, 2010. https://doi.org/10.1515/IJNSNS.2010.11.7.503
- [20] Z. Ma, Z. Liu, and G. Zhang, "Generalized synchronization of discrete systems," *Appl. Math. Mech.*, vol. 28, pp. 609-614, 2007. https://doi.org/10.1007/s10483-007-0506-y

- [21] L. Kocarev and U. Parlitz, "Generalized synchronization, predictability, and equivalence of unidirectionally coupled dynamical systems," *Phys. Rev. Lett.*, vol. 76, pp. 1816-1819, 1996. https://doi.org/10.1103/PhysRevLett.76.1816
- [22] X. He, C. Li, J. Huang, and L. Xiao, "Generalized synchronization of arbitrary dimensional chaotic systems," *Optik*, vol. 126, no. 4, pp. 454-459, 2015. https://doi.org/10.1016/j.ijleo.2014.09.005
- [23] J. Yan and C. Li, "Generalized projective synchronization of a unified chaotic system," *Chaos, Solitons and Fractals*, vol. 26, pp. 1119-1124, 2005. https://doi.org/10.1016/j.chaos.2005.02.034
- [24] D. Xu, "Control of projective synchronization in chaotic systems," Phys. Rev. E., vol. 63, pp. 027201-027204, 2001. https://doi.org/10.1103/PhysRevE.63.027201
- [25] G. Wen and D. Xu, "Nonlinear observer control for full-state projective synchronization in chaotic continuous-time systems," *Chaos, Solitons and Fractals*, vol. 26, no. 1, pp. 71-77, 2005. https://doi.org/10.1016/j.chaos.2004.09.117
- [26] J. Yan and C. Li, "Generalized projective synchronization of a unified chaotic system," *Chaos, Solitons and Fractals*, vol. 26, no. 4, pp. 1119-1124, 2005. https://doi.org/10.1016/j.chaos.2005.02.034
- [27] Z. Li, and D. Xu, "A secure communication scheme using projective chaos synchronization," *Chaos, Solitons and Fractals,* vol. 22, no. 2, pp. 477-481, 2004. https://doi.org/10.1016/j.chaos.2004.02.019
- [28] G. H. Li, "Modified projective synchronization of chaotic systems," *Chaos, Solitons and Fractals*, vol. 32, no. 5, pp. 1786-1790, 2007. https://doi.org/10.1016/j.chaos.2005.12.009
- [29] Y. Chen and X. Li., "Function projective synchronization between two identical chaotic systems," *International journal of modern physics C*, vol. 18, no. 5, pp. 883-888, 2007. https://doi.org/10.1142/S0129183107010607
- [30] X. Wang and Y. Wang, "Adaptive control for synchronization of a four-dimensional chaotic system via a single variable," *Nonliner Dyn.*, vol. 65, pp. 311-316, 2011. https://doi.org/10.1007/s11071-010-9893-1
- [31] X. Chen, L. Xiao, S. T. Kingni, I. Moroz, Z. Wei, and H. Jahanshahi, "Coexisting attractors, chaos control and synchronization in a self-exciting homopolar dynamo system," *International Journal of Intelligent Computing and* Cybernetics, vol. 13, no. 2, pp. 167-173, 2020. https://doi.org/10.1108/IJICC-11-2019-0123
- [32] Z. Wei, A. Yousefpour, H. Jahanshahi, U. E. Kocamaz, and I. Moroz, "Hopf bifurcation and synchronization of a five-dimensional self-exciting homopolar disc dynamo using a new fuzzy disturbance-observer-based terminal sliding mode control," *Journal of the Franklin* Institute, vol. 358, no. 1, pp. 814-833, 2021. https://doi.org/10.1016/j.jfranklin.2020.11.011